

SAFETY DATA SHEET

Creation Date 27-Apr-2009

Revision Date 18-Jan-2018

Revision Number 6

1. Identification

Product Name

Methanol

Cat No.:

A434-20; A450-4; A455-1; A457-4; LCMSKIT; OPTIMAKIT; SC95-1;

SW2-1; TIA947-4; TIA947P-200L; HC4001GAL; 22-050-135; 22-110-675;

22-110-887

CAS-No

67-56-1

Synonyms

Methyl alcohol:

Recommended Use

Laboratory chemicals.

Uses advised against

Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Fisher Scientific One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100

Emergency Telephone Number

CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Acute oral toxicity

Category 2 Category 3

Acute dermal toxicity

Category 3

Acute Inhalation Toxicity - Vapors

Category 3 Category 1

Specific target organ toxicity (single exposure)

Category 1

Target Organs - Optic nerve.

Specific target organ toxicity - (repeated exposure)

Target Organs - Kidney, Liver, spleen, Blood.

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor Toxic if swallowed Toxic in contact with skin Toxic if inhaled

Causes damage to organs

Causes damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Response

IF exposed: Call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician

Skin

Call a POISON CENTER or doctor/physician if you feel unwell

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Rinse mouth

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. Cannot be made non-poisonous.

WARNING. Reproductive Harm - https://www.p65warnings.ca.gov/.

3. Composition/Information on Ingredients

Component	CAS-No	VA/=:b+ 0/
Methyl alcohol		Weight %
The state of the s	67-56-1	>95

4. First-aid measures

Methanol

Revision Date 18-Jan-2018

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if

victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate

medical attention is required.

Ingestion Do not induce vomiting. Call a physician or Poison Control Center immediately.

Most important symptoms and

effects Notes to Physician

Breathing difficulties. May cause blindness: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed

containers exposed to fire with water spray.

Unsuitable Extinguishing Media Water may be ineffective

Flash Point 12 °C / 53.6 °F

Method -No information available

Autoignition Temperature 455 °C / 851 °F

Explosion Limits

Upper 31.00 vol % Lower 6.0 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable, Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO) Formaldehyde

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health Flammability Instability Physical hazards 3 0 N/A

6. Accidental release measures

Personal Precautions Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use

personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Take precautionary measures against static discharges.

Environmental Precautions Should not be released into the environment. See Section 12 for additional ecological information.

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

Up

Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling

Wear personal protective equipment. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not ingest. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Flammables area.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	14 : 05: (50:
Methyl alcohol	TWA: 200 ppm STEL: 250 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 260 mg/m³ (Vacated) STEL: 250 ppm (Vacated) STEL: 325 mg/m³ Skin TWA: 200 ppm TWA: 260 mg/m³	iDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m³ STEL: 250 ppm STEL: 325 mg/m³	Mexico OEL (TWA) TWA: 200 ppm TWA: 260 mg/m³ STEL: 250 ppm STEL: 310 mg/m³

<u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof

electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers

are close to the workstation location.

Personal Protective Equipment

Eye/face Protection

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

9. Physical and chemical properties

Physical State Appearance Odor

Odor Threshold

pΗ

Melting Point/Range **Boiling Point/Range**

Flash Point

Liquid Coloriess Alcohol-like

No information available

Not applicable -98 °C / -144.4 °F

64.7 °C / 148.5 °F @ 760 mmHg

12 °C / 53.6 °F

Evaporation Rate

Flammability (solid,gas)

Flammability or explosive limits

Upper

Lower Vapor Pressure

Vapor Density Specific Gravity

Solubility

Partition coefficient; n-octanol/water

Autoignition Temperature Decomposition Temperature

Viscosity

Molecular Formula Molecular Weight VOC Content(%)

Surface tension

5.2 (ether = 1) Not applicable

31.00 vol % 6.0 vol %

128 hPa @ 20 °C

1.11 0.791

Miscible with water No data available 455 °C / 851 °F No information available

0.55 cP at 20 °C

C H4 O 32.04 100

0.02255 N/m @ 20°C

10. Stability and reactivity

Reactive Hazard

None known, based on information available

Stability

Stable under normal conditions.

Conditions to Avoid

Incompatible products. Heat, flames and sparks. Keep away from open flames, hot

surfaces and sources of ignition.

Incompatible Materials

Strong oxidizing agents, Strong acids, Acid anhydrides, Acid chlorides, Strong bases,

Metals, Peroxides

Hazardous Decomposition Products Carbon monoxide (CO), Formaldehyde

Hazardous Polymerization

Hazardous polymerization does not occur.

Hazardous Reactions

None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information Component Information

Component	I DEC C		
	LD50 Oral	LD50 Dermal	i CEO Inhalati
Methyl alcohol	Calc. ATE 60 mg/kg		LC50 Inhalation
		Calc. ATE 60 mg/kg	Calc. ATE 0.6 mg/L (vapours) or
	LD50 > 1187 - 2769 mg/kg (Rat)	D50 = 17100 mg/kg (D-kk/k)	
	ingrity (ituit)	LD50 = 17100 mg/kg (Rabbit)	0.5 mg/L (mists)
		·	LC50 = 128.2 mg/L (Rat) 4 h
Tovicologically			LC3U = 1/8 / ma/L / Ref 1 / 6 1

Toxicologically Synergistic

Products

Carbon tetrachloride

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation

May cause skin and eye irritation

Sensitization

No information available

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTD	T			
Methyl alcohol	67-56-1		NTP	ACGIH	OSHA	Mexico	ı
Mutagenic Effects	07-00-1	Not listed	Not listed	Not listed	Not listed	Not listed	ı
marageine Ellecia		No information ava	ailahla				

No information available

Reproductive Effects

No information available.

Developmental Effects

Component substance is listed on California Proposition 65 as a developmental hazard.

Teratogenicity

No information available.

STOT - single exposure

Optic nerve

STOT - repeated exposure

Kidney Liver spleen Blood

Aspiration hazard

No information available

Symptoms / effects,both acute and May cause blindness: Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information

No information available

Other Adverse Effects

The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Component	Freshwater Algae	Faraland #1		
Methyl alcohol		Freshwater Fish	Microtox	Water Flea
mount alconor	Not listed	Pimephales promelas: LC50	EC50 = 39000 mg/L 25 min	EC50 > 10000 mg/L 24h
		> 10000 mg/L 96h	EC50 = 40000 mg/L 15 min	2000 - 10000 Hig/L 24H
Paraieten I D			EC50 = 43000 mg/L 5 min	1

Persistence and Degradability

Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation

No information available.

Mobility

Will likely be mobile in the environment due to its volatility.

Component	
Methyl alcohol	log Pow
ivieury aiconol	-0.74

13. Disposal considerations

Waste Disposal Methods

Should not be released into the environment.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67-56-1	U154	- TOTA - F Series Wastes

14. Transport information

DOT

UN-No

UN1230

Proper Shipping Name

METHANOL

Hazard Class

3

Packing Group

Ħ

TDG

UN-No

UN1230

Proper Shipping Name Hazard Class

METHANOL

Subsidiary Hazard Class

3

6.1

Packing Group

IATA

UN-No

UN1230

Proper Shipping Name

METHANOL

Hazard Class

3

Subsidiary Hazard Class

6.1 11

Packing Group

IMDG/IMO

Methanol

UN-No

Proper Shipping Name

UN1230 **METHANOL**

Hazard Class

Subsidiary Hazard Class

6.1

Packing Group

П

15. Regulatory information

International Inventories

ļ	Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICC	15000		,
	Methyl alcohol	Х	X		200-659-6		112	11003	ENCS	AICS	IECSC	KECL	
Ī	Legend:				200-000-0	L		X	X	X	X	X	ı

X - Listed

- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b)

Not applicable

SARA 313

Component			
Component	CAS-No	Weight %	SARA 313 - Threshold
		_	Values %
Methyl alcohol	67-56-1	>95	values /6
			1.0

SARA 311/312 Hazard Categories

See section 2 for more information

CWA (Clean Water Act)

Not applicable

Clean Air Act

Component	114 BA B .		
	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	X		Oldoe 2 Ozoffe Depletors
**************************************			-

OSHA Occupational Safety and Health Administration Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS ROs
Methyl alcohol	5000 lb	
California Proposition 65	This product contains the following proposition 65 cl	nemicals

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Cod
Methyl alcohol	67-56-1	Developmental	1 TOP GO NOILE	Category
II S State Dischards IV-		Developmental	-	Developmentai I

U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Methyl alcohol	Х	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): Υ **DOT Marine Pollutant** N **DOT Severe Marine Pollutant** Ν

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade

Serious risk, Grade 3

16. Other information

Prepared By

Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

Creation Date Revision Date

27-Apr-2009 18-Jan-2018 18-Jan-2018

Print Date Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS